
PORTABLE PIPE MARKER



Portable solution for permanent identification of pipe.



Maximum recommended character size is typically 1/4 of the pipe's diameter, not to exceed the stamper's 50mm x 90mm marking window. The adjustable fixture uses four compression springs to fit the stamper snugly onto pipe ranging from 0.75" to 10" diameter. Data to be marked can be entered on the unit's AC500 touchscreen controller or received from a host system or a bar code scanner for error-free product identification.

SPECIFICATIONS

| Marking Window | 50mm x 90mm (1.97" x 3.54") |
|-----------------------|--|
| Weight | 25 lbs |
| Dimensions | 15.9" W x 12.4" H x 9.2" D |
| Electric Supply | 90 – 250 VAC / 50-60 Hz |
| Air Supply | 60 – 90 PSI, clean and dry |
| Operating Environment | Humidity: 10 – 80% non-condensing Temperature: 32°F – 122°F |

| Interface | RS-232, RS-485, Ethernet TCP/IP, I/O, and USB |
|------------------|--|
| Memory | 64 MB internal memory |
| Languages | English, French, Spanish (others available) |
| Character Height | 1.5mm to maximum of window size |
| Fonts | 5x7, 11x16, OCR, 11x16 CH, AHSA, 2D Data Matrix, TrueType fonts |



10 4/10/08