

# PANNIER CORPORATION

207 Sandusky Street, Pittsburgh, PA 15212-5823 U.S.A.  
412.323.4900  
www.pannier.com

## Material Safety Data Sheet

Revision date: 9.24.2008

Revision 6.02

Page 1 of 5

### 1. Product Identification **AAK 0233 Ink**

**Commercial product name** AAK-0233

**Emergency telephone:** INFOTRAC 24-hour telephone # 1-800-535-5053

### 2. Hazards Identification

#### Routes of Entry

#### Signs and Symptoms of Exposure

Carcinogenicity (NTP):

Not Applicable

Carcinogenicity (IARC):

Isopropanol (CAS 67-63-0) is listed in group 3. Titanium dioxide (CAS 13463-67-7) is listed in group 3

Carcinogenicity (OSHA):

Not Applicable

#### 2.2 Special hazards for human health and environment

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Water risk class: 1  
Mild water pollutant. Low odour threshold. Irritating to respiratory system and skin. Symptoms: Nausea. Vomiting. Headache. Dizziness. Unconsciousness. Haemolysis liver function disorder kidney function disorder with Aspiration, it can result a pulmonary oedema and pneumonia.

### 3. Composition/Information on Ingredients

#### 3.2 Hazardous components

Components	CAS No.	Quantity
Acetone, propan-2-one, propanone	67-64-1	55-60%
Titanium dioxide	13463-67-7	10-15%
Butanone, ethyl methyl ketone	78-93-3	10-15%
Cellulose nitrate concentration <12.6% nitrogen	9004-70-0	5-10%
N-methyl-2-pyrrolidone	872-50-4	1-5%
Isopropanol, isopropyl alcohol, propan-2-ol	67-63-0	1-5%

### 4. First Aid Measures

**General Information:** In case of accident or if you feel unwell, seek medical advice immediately (show safety data sheet if possible). Take off immediately all contaminated clothing if victim is at risk of losing consciousness, position and transport on their side. The decision about the measures, which have to be initiated, has to be taken by the doctor.

4.1 **After inhalation:** In case of accident by inhalation: remove casualty to fresh air and keep at rest. Consult physician

4.2 **After contact with skin:** After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap.

4.3 **After contact with eyes:** Take off lenses. Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Consult physician.

4.4 **After ingestion:** Calm the victim. Rinse mouth thoroughly with water. Immediately get medical attention. Let water be swallowed in little sips (dilution effect). Do not induce vomiting. Milk or fat oils and are strongly contraindicated. Do not allow a neutralisation agent to be drunk.

### 5. Fire Fighting Measures

5.1 **Suitable extinguishing media:** alcohol resistant foam. Carbon dioxide (CO<sub>2</sub>). Dry extinguishing powder. Water spray. Atomized water.

5.2 **Unsuitable extinguishing media:** High power water jet

5.3 **Special hazards arising from the chemical:** In case of fire may form: Carbon monoxide. Nitrogen oxides (NO<sub>x</sub>). Vapours may form explosive mixtures with air.

5.4 **Protective equipment and precautions for firefighters:** Wear a self-contained breathing apparatus and chemical resistant suit.

5.5 **Additional information:** Temperature class T 1 (Ignition temperature: >450 °C)

### 6. Accidental Release Measures

6.1 **Personal precautions:** Provide fresh air. Avoid contact with skin and eyes. Wear suitable gloves. NR (Natural rubber (Caoutchouc), Natural latex). NBR (Nitrile rubber) limited resistance, Butyl rubber. In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves. Wear eye/face protection. If technical suction or ventilation measures are not possible or are insufficient, protective breathing apparatus must be worn. The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when

# PANNIER CORPORATION

207 Sandusky Street, Pittsburgh, PA 15212-5823 U.S.A.

412.323.4900

www.pannier.com

## Material Safety Data Sheet

Revision 6.02

Page 2 of 5

Revision date: 9.24.2008

handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used. See protective measures under point 7 and 8.

**6.2 Environmental precautions:** Due to danger of explosion, prevent leakage of vapors into cellars, flues and ditches. Do not empty into drains or the aquatic environment. Explosion hazard.

**6.3 Methods for cleaning up/taking up:** Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated objects and areas thoroughly observing environmental regulations. Treat the assimilated material according to the section on waste disposal. (13)

**6.4 Additional information:** Keep away from sources of ignition. No smoking. Do not breathe gas/fumes/vapour/spray. The product is partially water mixable.

### 7. Handling and Storage

**7.1 Advice on safe handling:** When handling with chemicals, please consider usual precautionary measures. Wear suitable protective clothing, gloves and eye/face protection. See protective measures under point 7 and 8. Do not leave the container open. Handle open container with care. Keep container tightly closed. If technical suction or ventilation measures are not possible or are insufficient, protective breathing apparatus must be worn. When using do not eat, drink or smoke. Protect skin by using skin protective cream. "Wash hands when done working with material; at breaks, lunch, shift changes, etc." Keep away from food, drink and animal feeding stuffs. Never clean the skin or the clothes with the preparation!

**7.2 Advice on protection against fire and explosion:** The vapours are heavier than air and can accumulate in high concentrations on the ground, in cavities, channels and cellars. In use, may form flammable/explosive vapour-air mixture. Take precautionary measures against static discharges. Keep away from sources of ignition. No smoking. Highly flammable.

**7.3 Further information on handling:** Vapours / aerosols should be extracted by suction directly at point of origin. See information supplied by the manufacturer. For limiting the emission through volatile organic compounds (VOC), the solvent vapours should be forwarded to an emission control facility. Please note the manufacturer indications for storage conditions and shelf life (see section 7.3). When storing outside the recommended storing temperatures, the shelf life can be shortened. Inappropriate storage may conduct to endangerment of persons and environment.

**7.4 Requirements for storage rooms and vessels:** Keep only in the original container in a cool, well ventilated place. Keep container tightly closed. Use appropriate containers, e.g. UN-approved HDPE or thin sheet packing, for decanting. In partially or completely disposed containers, there can be an accumulation of a potentially explosive atmosphere in their head space. - Rooms, in which inks are stocked, have to be equipped with sufficient air ventilation. Remove all sources of ignition. Protect against high warming or solar radiation. Recommended storage temperature: +15 °C - 25 °C. Highly flammable. Maximum period of storage (time): 9 months

### 8. Exposure Controls/Personal Protection:

#### 8.1 Exposure limit values:

##### Exposure Limits

Components	CAS No.	ml/m <sup>3</sup>	mg/m <sup>3</sup>	Category	Origin
2-Butanone	78-93-3	200	590	TWA (8hr)	REL
		300	885	STEL (15 min)	REL
2-Butanone (Methyl ethyl ketone)	78-93-3	200	590	TWA (8hr)	REL
		1000	2400	TWA (8hr)	REL
Acetone	67-64-1	250	590	TWA (8hr)	REL
		400	980	TWA (8hr)	REL
Isopropyl alcohol	67-63-0	400	980	TWA (8hr)	REL
		500	1225	STEL (15 min)	REL
Titanium dioxide	13463-67-7	n/a	n/a	TWA (8hr)	REL
		13463-67-7	n/a	TWA (8hr)	REL
Titanium dioxide Total dust	13463-67-7	n/a	15	TWA (8hr)	REL

##### Exposure controls:

**Occupational exposure controls** Technical measures and the application of appropriate methods of operation, as indicated in section 7, have precedence over to the application of personal protection equipment.

**8.2 Protective and hygiene measures:** Protect skin by using skin protective cream. Wash hands when done working with material; at breaks, lunch, shift changes, etc.

**8.3 Respiratory protection:** If technical suction or ventilation measures are not possible or are insufficient, protective breathing apparatus must be worn.

Respiratory filter A1 (brown) up to 1000 mL / m<sup>3</sup> (ppm)

Respiratory filter A1 (brown) up to 5000 mL / m<sup>3</sup> (ppm)

Respiratory filter A1 (brown) up to 10000 mL / m<sup>3</sup> (ppm)

**8.4 Hand protection:** Type of chemical protective gloves to choose depends on the concentration and quantity of dangerous substances as well as on work place specifications. In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

**8.5 Eye protection:** Tightly sealed safety glasses.

**8.6 Skin protection:** Carry long-sleeved, flame impeding and anti-static labor safety clothing

# PANNIER CORPORATION

207 Sandusky Street, Pittsburgh, PA 15212-5823 U.S.A.  
412.323.4900  
www.pannier.com

## Material Safety Data Sheet

Revision date: 9.24.2008

Revision 6.02 Page 3 of 5

**8.7** Environmental exposure controls: Please see chapter 6 and 7

**8.8** Additional advice on control parameters: Not Applicable

### **9. Physical and Chemical Properties**

#### **9.1 Appearance**

Form: liquid  
Color: white  
Odor: like acetone

#### **9.2 Important health, safety and environmental information**

pH-Value (at 20 °C):	not determined	DIN 19268
Melting point:	not determined	DIN 53181
Boiling point:	79 – 110°C	DIN 51751
Flash point:	-18°C	DIN51765
Explosive properties	Vapours may form explosive mixtures with air	
Lower explosion limits:	2.6 vol %	DIN51649
Upper explosion limits:	13 vol %	DIN51649
Oxidizing properties	not determined	
Vapor pressure (at 20°C)	233 hPa	DIN51754
Density (at 20°C)	0.96 g/cm <sup>3</sup>	DIN53217
Water solubility (at 20oC)	250 g/L	
Partition coefficient	not determined	
Viscosity/dynamic (at 20oC)	5.8 mPas	DIN 53018
Viscosity/Kinematic (at 20oC)	not determined	
Vapor density: (at 20oc)	>1	
Evaporation rate (at 20oC)	not determined	
Solvent separation test	not determined	

#### **9.3 Other information**

Ignition temperature:	465oC	DIN51794
VOC	75.3% (722.88 g/l)	
Maximum period of storage (time):	9 months	

### **10 Stability and Reactivity**

**10.1** Stability: Stable

**10.2** Conditions to avoid: High warming > 45°C and / or solar radiation. Heating up forwards the transit of liquid to the vapour phase and the accumulation of potentially explosive atmosphere.

**10.3** Materials to avoid: Keep away from strong acids, leachates, heavy metal salts and reducing materials

**10.4** Hazardous decomposition products: Keep away from strong acids, leachates, heavy metal salts and reducing materials.

**10.5** Possibility of Hazardous Reactions: Not Applicable

**10.6** Additional information: This product is stable

### **11. Toxicological Information**

#### Acute toxicity

Acute toxicity, oral rat. LD50: 5800 mg / kg / acetone, propan-2-one  
Acute toxicity, dermal Rabbit. LD50: 20000 mg / kg acetone, propan-2-one  
Acute toxicity, inhalant rat. LC50: 50.1 mg / l / 8 h acetone, propan-2-one

Specific effects in experiment on an animal: For this product there are currently no toxicological data available.

Corrosive and irritant effects For this product there are currently no toxicological data available.

Sensitising effects For this product there are currently no toxicological data available.

Severe effects after repeated or prolonged exposure For this product there are currently no toxicological data available.

Carcinogenic/mutagenic/toxic effects for reproduction For this product there are currently no toxicological data available.

Additional information on tests For this product there are currently no toxicological data available.

Empirical data on effects on humans For this product there are currently no toxicological data available

Further information Prolonged/repetitive skin contact may cause skin defatting or dermatitis. Highly fat solubilising effect.  
Danger of cutaneous absorption. Inhalation may cause headache, drowsiness, somnolence and perception disorder. Eye contact may cause heavy irritation and oedema formation of the conjunctiva. May cause damage on liver, kidneys and nervous system. Aspiration after swallowing and vomiting may conduct to heavy lung damages.

### **12 Ecological Information**

#### **12.1 Ecotoxicity**

Bacterial toxicity: Pseudomonas putida: EC50: 1700 mg / l / 16 h / acetone, propan-2-one, propanone  
Acute Daphnia toxicity Daphnia magna: LC50: 12600 - 12700 mg / l / 48 h / acetone, propan-2-one, propanone

# PANNIER CORPORATION

207 Sandusky Street, Pittsburgh, PA 15212-5823 U.S.A.

412.323.4900

www.pannier.com

## Material Safety Data Sheet

Revision 6.02 Page 4 of 5

Revision date: 9.24.2008

- 12.2** **Mobility:** Liquids Partly soluble with water. The hazardous ingredients evaporate rapidly, when you clear them to the environment. In grounds: a moderate to high mobility of the solvents used in the preparation can be expected.
- 12.3** **Persistence and degradability:** Dangerous components: Solvents are biologically degradable. The used colorants are difficult to dissolve in water. Colorants are, according to regulations, very resistant and therefore, under the conditions of clarification plants or surface water poorly bio-degradable
- 12.4** **Bioaccumulative potential:** No indication of bio-accumulation potential
- 12.5** **Other adverse effects:** Water risk class: 1 Mild water pollutant
- 12.6** **Further information:** Eco-toxicological data have not been identified especially for this preparation. The indicated information is based on the current state of knowledge of the used materials and of similar products. It should not reach the canalization, the ground or the waters. With an appropriate handling and application any ecological problems are not to be expected.

**13** **Disposal Considerations:**

- 13.2** **Contaminated packaging:** Waste disposal according to official state regulations.

**14** **Transport Information**

**14.1** **DOT Classification:**

Proper shipping name:	Paint
Hazard Class:	3
UN/NA:	UN 1263 PG II

**14.2** **Transport regulations cited according to international regulations.**

**Land transport (ADR/RID)**

UN number	1263
ADR/RID class:	3
Classification Code	F1
Hazard-no.:	33
Hazard label:	3
ADR/RID packing group:	II
Limited quantity:	LQ6
Description of the goods	PAINT UN 1263
Special regulations: 163 640D 650	
Transport category: 2	
Tunnel restriction code: D1E	

**Remarks**

**Inland waterways transport**

UN number	1263
ADR/RID class:	3
Classification Code	F1
Hazard label:	3
Packing group:	II
Limited quantity:	LQ6
Description of the goods	PAINT UN 1263
Special regulations: 163 640D 650	

**Remarks**

**Marine transport**

UN number	1263
IMDG code:	3
Marine pollutant	No
Hazard label:	3
IMDG Packing group:	II
EmS	F-E, S-E
Limited quantity:	5 L
Description of the goods	PAINT UN 1263
Special regulations: 163, 944	

**Remarks**

**Air transport**

UN/ID number	1263
ICAO/IATA-DGR	3
Hazard label:	3
ICAO packing group	II
Limited quantity Passenger	1L
IATA-packing instructions – Passenger	305
IATA max quantity – Passenger	5L
IATA packing instructions – Cargo	307
IATA max quantity – Cargo	60L
Description of the goods	PAINT UN 1263

# PANNIER CORPORATION


207 Sandusky Street, Pittsburgh, PA 15212-5823 U.S.A.  
412.323.4900  
www.pannier.com

## Material Safety Data Sheet

Revision date: 9.24.2008

Revision 6.02 Page 5 of 5

- 15** Remarks Passenger LQ Y305  
Regulatory Information Special regulations A72  
U.S. Regulations:  
SARA Section 313 Toxic Release Chemicals  
Methyl ethyl ketone (CAS 78-93-3)  
N-methyl-2-pyrrolidone (CAS 872-50-4)  
Additional information DO NOT USE THIS PRODUCT FOR CLEANING SKIN AND CLOTHES!
- 16** Other Information  
Hazardous Materials Information Label (HMIS)  
Health: 1  
Flammability: 3  
Physical Hazard: 0  
NFPA Hazard Ratings  
Health: 1  
Flammability: 3  
Reactivity: 0  
Unique Hazard: Not Applicable



Only for industrial application - not for private use.

### Disclaimer of Liability

THE INFORMATION IN THIS MSDS WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, REGARDING ITS ACCURACY OR CORRECTNESS. THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE AND DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.