

PANNIER CORPORATION
207 Sandusky Street, Pittsburgh, PA 15212-5823 U.S.A.
Material Safety Data Sheet



Revision date: 9/1/2011

Revision 1.10

Page 1 of 4

Material Safety Data Sheet

SECTION 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Name: CL-TKD Cleaner

Company PANNIER CORPORATION
412-323-4900
sales@pannier.com

Telephone INFOTRAC 24 hr telephone # 1-800-535-5053

SECTION 2 HAZARDS IDENTIFICATION

Emergency Overview

Danger	Highly flammable.
State of matter	liquid colourless
Odour	Mint-like

Potential environmental effects

Environmental precautions: Should not be released into the environment. Prevent further leakage or spillage if safe to do so.

Ecological information: See chapter 12

Potential health effects

Acute effects

Eyes

Causes eye irritation.

Skin

Prolonged or repeated contact with liquid may cause defatting resulting in drying, redness and possible blistering

Inhalation

May cause respiratory tract irritation

Ingestion

Aspiration hazard if swallowed - can enter lungs and cause damage

Toxicological information:

See chapter 11

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

Components

Butanone, ethyl methyl ketone

CAS-No.

78-93-3

Weight %

99.50

Exposure limit(s): See chapter 8

Classification and hazard labeling: See chapter 15

SECTION 4 FIRST AID MEASURES

Eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician

Skin contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before re-use. If skin irritation persists, call a physician.

Inhalation

Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.

Ingestion

If swallowed, seek medical advice immediately and show this container or label. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

SECTION 5 FIRE-FIGHTING MEASURES

Flammability

Flash point

-9 °C

Auto ignition temperature

515 °C

Explosion limits

Lower explosion limit: 1.4 %(V)

Upper explosion limit: 11.4 %(V)

Fire/explosion

Vapours may form explosive mixtures with air. Flash back possible over considerable distance

Hazardous combustion products

Carbon oxides

Suitable extinguishing media

Water spray

Alcohol-resistant foam

Dry chemical

Carbon dioxide (CO₂)

Unsuitable extinguishing media

No information available

Protection measures and instructions

Wear self-contained breathing apparatus and protective suit.

Further information

Cool containers / tanks with water spray.

PANNIER CORPORATION

207 Sandusky Street, Pittsburgh, PA 15212-5823 U.S.A.

Material Safety Data Sheet

Revision date: 9/1/2011

Revision 1.10

Page 2 of 4

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions Keep people away from and upwind of spill/leak. Remove all sources of ignition. Do not breathe vapours or spray mist. Material can create slippery conditions.

Environmental precautions Should not be released into the environment. Prevent further leakage or spillage if safe to do so

Methods for cleaning up Soak up with inert absorbent material and dispose of as hazardous waste.

Exposure controls / personal protection: See chapter 8

SECTION 7 HANDLING AND STORAGE

Safe handling advice Provide sufficient air exchange and/or exhaust in work rooms. Wear personal protective equipment. Ensure all equipment is electrically grounded before beginning transfer operations. Take precautionary measures against static discharges

Advice on protection against fire and explosion Keep away from heat and sources of ignition. Use explosion-proof equipment

Storage Keep containers tightly closed in a dry, cool and well-ventilated place.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures Provide sufficient air exchange and/or exhaust in work rooms.

Personal protective equipment

Eyes Safety glasses with side-shields

Skin Protective suit Safety shoes

Inhalation In case of insufficient ventilation, wear suitable respiratory equipment

Hand protection Gloves suitable for permanent contact:
Material: butyl-rubber
Break through time: 4 H
Material thickness: 0.5 mm
Unsuitable gloves:
Material: Polyvinylchloride, leather, nitrile rubber / nitrile latex
Natural rubber / natural latex.

Hygiene measures Wash hands before breaks and immediately after handling the product.

Protective measures Wear suitable protective equipment

Exposure Guidelines

Components Exposure limit(s)

2-BUTANONE

US. ACGIH Threshold Limit Values time weighted average 200 ppm
US. ACGIH Threshold Limit Values Short term exposure limit 300 ppm
US. NIOSH: Pocket Guide to Chemical Hazards Recommended exposure limit (REL): 200 ppm (590 mg/m³)
US NIOSH Pocket Guide to Chemical Hazards Short term exposure limit 300 ppm (885 mg/m³)
US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Permissible exposure limit 200 ppm (590 mg/m³)
US. OSHA Table Z-1-A (29 CFR 1910.1000) time weighted average 200 ppm (590 mg/m³)
US. OSHA Table Z-1-A (29 CFR 1910.1000) Short term exposure limit 300 ppm (885 mg/m³)
US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants Time Weighted Average (TWA) Permissible Exposure Limit (PEL): 200 ppm (590 mg/m³)
US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants Short term exposure limit 300 ppm (885 mg/m³)
EU. Indicative Exposure and Directives relating to the protection of risks related to work exposure to chemical, physical, and biological agents. time weighted average 200 ppm (600 mg/m³)
EU Indicative Exposure and Directives relating to the protection of risks related to work exposure to chemical, physical and biological agents. Short term exposure limit 300 ppm (900 mg.m³)

PEL= Permissible Exposure Limits
TLV= Threshold Limit Value
EL= Excursion Limit

TW Time Weighted Average (8 hr.)
STEL= Short Term Exposure Limit (15 min.)
WEEL= Workplace Environmental Exposure Level

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

State of matter liquid

Colour colourless

Odour mint-like

Form liquid

Boiling point/boiling range 79.6 °C

Flash point -9 °C closed cup 9°C open cup

Lower explosion limit 1.4 %(V)

PANNIER CORPORATION
207 Sandusky Street, Pittsburgh, PA 15212-5823 U.S.A.
Material Safety Data Sheet

Revision date: 9/1/2011

Revision 1.10

Page 3 of 4

Upper explosion limit	11.4 %(V)
Vapour pressure	121.323 mPa at 25 °C
Solubility	partly miscible
Viscosity	0.51 mm ² /s
Viscosity dynamic	0.41 mPa.s
Melting point/range	-86.3 °C
Density	0.805 g/cm ³
pH	no data available

SECTION 10 STABILITY AND REACTIVITY

Conditions to avoid	Heat, flames and sparks
Hazardous decomposition products	Carbon oxides
Incompatible products	Strong oxidizing agents Incompatible with acids. Halogenated compounds
Hazardous reactions	Hazardous polymerisation does not occur.

SECTION 11 TOXICOLOGICAL INFORMATION

Acute oral toxicity	LD50 rat: 2737 mg/kg; literature value
Acute inhalation toxicity	LC50 rat: 23500 mg/kg; 8 h literature value
Acute dermal toxicity	LD50 rabbit: 6480 mg/kg; literature value
Skin irritation	rabbit: moderately irritating; literature value
Eye irritation	rabbit: irritating; literature value

SECTION 12 ECOLOGICAL INFORMATION

Ecotoxicity effects	
Toxicity to fish	LC50 Bluegill sunfish: 4,467 mg/l; 96 h; literature value LC50Poecilia reticulata: 5,700 mg/l; 24 h; literature value
Toxicity to daphnia	LC50 Pimephales promelas: 3,200 mg/l; 96H; literature value
Toxicity to algae	EC50 Daphnia magna: < 520 mg/l; 48 h; literature value

SECTION 13 DISPOSAL CONSIDERATIONS

Waste Classification	US. EPA Resource Conservation and Recovery Act: (RCRA) D List of Characteristic Hazardous Wastes (40 CFR 261.21-24): D001
Waste from residues / unused products	In accordance with local and national regulations. .Do not contaminate ponds, waterways or ditches with chemical or used container. The product should not be allowed to enter drains, water courses or the soil.
Uncleaned empty packaging:	Do not burn, or use a cutting torch on, the empty drum. Triple rinse containers., Can be offered for recycling, re-conditioning or puncture.
Handling and storage:	See chapter 7
Exposure controls / personal protection:	See chapter 8

SECTION 14 TRANSPORT INFORMATION

DOT/49CFR	UN 1193 Methyl ethyl ketone, 3, II
ADR	UN 1193 Methyl ethyl ketone, 3, II
RID	UN 1193 METHYL ETHYL KETONE, 3, II
ADNR	UN 1193 METHYL ETHYL KETONE, 3, II
IMDG	UN 1193 METHYL ETHYL KETONE, 3, II, EmS F-E, S-D
ICAO/IATA	UN 1193 Methyl ethyl ketone, 3, II

SECTION 15 REGULATORY INFORMATION

U.S. Federal Classifications:

OSHA Hazards Flammable Liquid, Mild eye irritant, Mild eye irritant
SARA 311/312 Fire Hazard, Acute Health Hazard

U.S. Regulated Ingredients:

Hazard information reporting

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required

Components

Butanone

CAS-No.

78-93-3

US. Massachusetts Commonwealth's Right-to-Know Law (Appendix A to 105 Code of Massachusetts Regulations Section 670.000)

Components

CAS-No.

PANNIER CORPORATION
207 Sandusky Street, Pittsburgh, PA 15212-5823 U.S.A.
Material Safety Data Sheet

Revision date: 9/1/2011

Revision 1.10

Page 4 of 4

Butanone

78-93-3

US. New Jersey Community Right-To-Know Survey, Table A: NJ Environmental Hazardous Substances [EHS] List (N.J. Admin. Code Title 7 Section 1G-2.1)

Components

CAS-No.

Butanone

78-93-3

US. Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323)

Components

CAS-No.

Butanone

78-93-3

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

Spill reporting

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Components

CAS-No.

Reportable Quantity

Butanone

78-93-3

5,000 lbs

Health

US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)

Components

CAS-No.

Not listed

Inventories

EU list of existing chemical substances

All chemical constituents are listed in: EU list of existing chemical substances (See chapter 3)

US TSCA Inventory

All chemical constituents are listed in: US TSCA Inventory (See chapter 3)

Australian Inv. of Chem. Substances AICS

All chemical constituents are listed in: Australian Inv. of Chem. Substances AICS (See chapter 3)

Canadian Domestic Substances List DSL

All chemical constituents are listed in: Canadian Domestic Substances List DSL (See chapter 3)

Jap. Inv. of Exist. & New Chemicals ENCS

All chemical constituents are listed in: Jap. Inv. of Exist. & New Chemicals ENCS (See chapter 3)

Korean Exist. Chemicals List ECL

All chemical constituents are listed in: Korean Exist. Chemicals List ECL (See chapter 3)

Philippines Inv. of Chem. Subst. PICCS

All chemical constituents are listed in: Philippines Inv. of Chem. Subst. PICCS (See chapter 3)

Inv. of Exist. Chem. Substances in China

All chemical constituents are listed in: Inv. of Exist. Chem. Substances in China (See chapter 3)

Other international regulations

WHMIS Classification B2: Flammable Liquid

SECTION 16 OTHER INFORMATION

Hazard Ratings

	Health	Fire	Reactivity Hazard
HMIS	1	3	0
NFPA	1	3	0

Disclaimer of Liability

THE INFORMATION IN THIS MSDS WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, REGARDING ITS ACCURACY OR CORRECTNESS. THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE AND DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.