# **SAFETY DATA SHEET**

## Section 1 - Chemical Product and Company Information



#### **PANNIER CORPORATION**

207 Sandusky Street Pittsburgh, PA 15212-5823 USA

#### www.pannier.com

Information Telephone: 412-323-4900

Email: sales@pannier.com Infotrac: 800-535-5053

Product Code: D-1213

Product Name: BRT WHITE INK Product Use: Jet Printer Ink

Not recommended for: Consumer Use

### Section 2 - Hazards Identification

CHC	Ratin	ae

Flammable liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)
Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: >=

2.3 < 4.0 or persistent inflammation

Respiratory sensitizer 1 Respiratory sensitizer

Skin sensitizer 1 Skin sensitizer

Aspiration hazard 1 Aspiration Toxicity Category 1: Known (regarded)- human

evidence - hydrocarbons with kinematic viscosity? 20.5

mm2/s at 40° C.

#### **GHS Hazards**

H225 Highly flammable liq	uid and vapor
---------------------------	---------------

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### **GHS Precautions**

P210	Keep away from heat/	sparks/open flames/h	not surfaces. No smoking
1 2 10	ILCCD away IIOIII IICau	3Dair3/UDCII IIaiiiC3/I	ioi suriaces. No sirionirio

P233 Keep container tightly closed

P240 Ground/bond container and receiving equipment

P241 Use explosion-proof electrical/ventilating/light/manufacturer/equipment

P242 Use only non-sparking tools

P243 Take precautionary measures against static discharge
P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P264 Wash contact area thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace P280 Wear protective gloves/protective clothing/eye protection/face protection

P285 In case of inadequate ventilation wear respiratory protection

P321 Specific treatment (see supplemental first aid instruction on this label)

P331 Do NOT induce vomiting

P362 Take off contaminated clothing and wash before reuse

P363 Wash contaminated clothing before reuse

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/...

P302+P352 IF ON SKIN: wash with plenty of water.

P303+P361+P353 IF ON SKIN (or hair): Take off Immediately all contaminated clothing. Rinse SKIN

with water [or shower].

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a

position comfortable for breathing.

SDS for: D-1213 Page 1 of 8

P332+P313 If skin irritation occurs: Get medical advice/attention.

P333+P313 IF SKIN irritation or rash occurs: Get medical advice/attention.

P342+P311 IF experiencing respiratory symptoms: Call a POISON CENTER/doctor/...

P370+P378 In case of fire: Use ... to extinguish.

P405 Store locked up

P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container in accordance with

local/regional/national/international regulations.

Signal Word: Danger



**Acute Toxicity** 

N/A

**Conditions Aggravated** 

N/A

**Chronic Effects** 

N/A

## Section 3 - Composition / Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Distillates, petroleum, light distillate hydrotreating process, low-boiling	68410-97-9	40.00%
Petroleum distillates, hydrotreated light	64742-47-8	29.00%
Naphtha, petroleum, hydrotreated light	64742-49-0	22.00%
Titanium (IV) dioxide	13463-67-7	6.00%
1,3-Butadiene, 2-methyl-, homopolymer	9003-31-0	3.00%

### Section 4 - First Aid Measures

INHALATION - Move affected person to fresh air, rest in a half upright position, and loosen clothing . If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Seek medical advice after significant exposure.

EYE CONTACT - Flush with large amounts of water for at least 15 minutes . Lift eyelids occasionally. Get prompt medical attention.

SKIN - Wash thoroughly with soap and water immediately. Remove all contaminated clothing immediately. Seek medical advice if irritation persists.

INGESTION - Seek medical advice. The decision to induce vomiting or not must be made by a physician after careful consideration of all materials ingested. Risk of aspiration into lungs.

### Section 5 - Fire Fighting Measures

### Suitable Extinguishing Media

Carbon Dioxide---Dry Chemical---Foam---Water Fog

SDS for: D-1213 Page 2 of 8

Use water for cooling material stored in vicinity of fire.

#### **Explosion Hazards**

Vapors are heavier than air and may travel along the ground to an ignition source some distance from material handling point. Ignition sources include pilot lights, smoking, heaters, electric motors, sparks from electrical switches and static discharges.

CAUTION: Never use cutting torch on empty containers! Residual solvent vapor in empty container may explode. Application to hot surfaces requires special precautions. During emergency conditions, overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain Medical Attention.

#### **Hazardous Combustion Products**

N/A

#### **Recommended Fire Equipment**

Use self-contained breathing apparatus with a full-face piece operated in a pressure-demand or other positive pressure mode. Wear protective clothing.

### Section 6 - Accidental Release Measures

<u>Non-emergency personnel:</u> Evacuate and isolate the area and prevent access. Remove ignition sources. No flares, smoking or flames in hazard area. Notify management. Avoid breathing vapor or mist and put on protective equipment. Control source of the leak. Ventilate.

<u>Emergency responders:</u> See section 8 for any specialized clothing recommendations. Also reference the information for non-emergency personnel

<u>Environmental precautions:</u> Prevent further leakage or spillage if possible. Do not allow the material to spread to drains, sewers, water supplies, or soil. Contact PANNIER for assistance and advice.

<u>Small Spill:</u> Stop leak if possible and move containers from the spill area. Water soluble: dilute with water and mop up. Water Insoluble: Cover spill area with a suitable absorbent inert material (Kitty Litter, Oil-Dri, etc.) and dispose of in an appropriate metal waste container. Dispose of material through a licensed waste disposal contractor.

<u>Large Spill:</u> Stop leak if possible and move containers from the spill area. Approach release from upwind. Contain spillage and with non-combustible absorbent material and place in appropriate disposal container according to local regulations. Dispose of material through a licensed waste disposal contractor. Report spill to appropriate governing agencies if applicable.

PANNIER requires that INFOTRAC be immediately notified when this product is unintentionally released from its container during its course of distribution, regardless of the amount released. Distribution includes transportation, storage incidental to transportation, loading and unloading. Such notification must be immediate and made by the person have knowledge of the release.

### Section 7 - Handling and Storage

#### **Precautions for Safe Handling**

Keep away from food, drink and heat. Keep away from sources of ignition. No smoking. Do not breathe vapor. Avoid contact with skin and eyes. Never use pressure to empty. Take precautionary measures against static discharges.

Storage temperature-

SDS for: D-1213 Page 3 of 8

Minimum: do not freeze Maximum: 40°C (104°F)

Storage Period- See technical data sheet.

Section 8 - Ex	posure Contr	rols / Persona	I Protection
----------------	--------------	----------------	--------------

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Distillates, petroleum, light distillate hydrotreating process, low-boiling 68410-97-9	Not Established	Not Established	Not Established
Petroleum distillates, hydrotreated light 64742-47-8	Not Established	Not Established	Not Established
Naphtha, petroleum, hydrotreated light 64742-49-0	Not Established	Not Established	Not Established
Titanium (IV) dioxide 13463-67-7	15 mg/m3 TWA (total dust)	10 mg/m3 TWA	N/A
1,3-Butadiene, 2-methyl-, homopolymer 9003-31-0	Not Established	Not Established	Not Established

Engineering Controls: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation, or other controls to keep air containment concentration below current applicable OSHA permissible exposure limit or ACGIH TLV limit, and volatiles below lower explosive limit. Heavy solvent vapors should be removed from the lower levels of area, and all ignition sources (non-explosion proof equipment) should be eliminated if flammable mixtures will be encountered. Remove decomposition products formed during welding or flame cutting of surfaces coated with this product. For baking finishes - vent vapors emitted on heating.

 $\underline{\textbf{Environmental Controls:}} \ \textbf{Emissions should comply with environmental protection legislation}.$ 

#### **Individual Protection Measures:**

<u>Hygiene measures</u>- Wash hands, forearms, etc. after handling chemical products, before eating, smoking, and using the lavatory, and the end of the work period. Use appropriate techniques when removing potentially contaminated clothing and wash before reusing. Know the locations of eyewash and safety showers.

Respiratory Protection- Provide adequate ventilation to keep exposure below permissible limits. If a risk assessment deems necessary, operator is to use a properly fitted, air purifying or supplied air respirator. Respirator selection must be based on known/ anticipated exposure levels, the hazards of the product, and the safe working limits of the respirator.

Skin and Body Protection-Wear chemical resistant gloves (nitrile) and paint suits when necessary, based on risk assessment. The most suitable glove must be chosen in consultation with the gloves supplier who can inform about the breakthrough time of the glove material. PPE for the body should be selected based on the risks of the task being performed and approved by a specialist. Appropriate footwear should also be approved.

Eye/Face Protection- Wear approved chemical safety goggles where exposure to vapor or contact with eyes is

SDS for: D-1213 Page 4 of 8

## Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties:

Viscosity: Not determined

% Weight Solids 8.62

VOC Wt/Gal (wet) 6.04

Specific Gravity (SG) 0.793

Odor Threshold: Not determined

Boiling Point: 185°C

LEL/UEL: N/A

Evaporation Rate (nBuAc=1): Not determined

Vapor Density: N/A

Partition coefficient: Not determined

pH: N/A

% Volume Solids 3.53

U.S. VOC Wt/Gal (wet) 6.04

Odor: Hydrocarbon

Color: White

Flash Point: 32°F.0°C

Autoignition Temperature: N/A

Vapor Pressure: N/A

Freezing Point: Not determined

### Section 10 - Stability and Reactivity

The following materials should be avoided in contact with the mixture

Strong acids

#### **Hazardous decomposition products**

Titanium/titanium oxides

## Section 11 - Toxicological Information

#### **Mixture Toxicity**

Oral Toxicity LD50: 3,733mg/kg Dermal Toxicity LD50: 3,139mg/kg

LC<sub>50</sub> and LD<sub>50</sub> toxicity for this product are merely estimates and have yet to be determined. For individual component ecotoxicity, please refer to Section 11.

#### **Possible Routes of Entry**

Inhalation Eye Contact Ingestion

#### **Potential Target Organs**

Respiratory System

#### **Effects of Overexposure**

Not Available

#### The following components are possible carcinogens

\*Materials labeled a carcinogen in dust form are supplied in solution, thus eliminating the hazard.

<u>CAS Number</u> <u>Description</u> <u>% Weight</u> <u>Carcinogen Rating</u>

13463-67-7 Titanium (IV) dioxide 6 Titanium (IV) dioxide: (\*dust)
NIOSH: potential occupational

carcinogen

IARC: Possible human carcinogen

OSHA: listed

SDS for: D-1213 Page 5 of 8

Distillates, petroleum, light distillate hydrotreating process, low-boiling distillate hydrotreating process, low-boiling: EU REACH: Present (P)

Naphtha, petroleum, hydrotreated light 22 Naphtha, petroleum, hydrotreated light: EU REACH: Present (P)

### Section 12 - Ecological Information

#### **Mixture Ecotoxicity**

Toxicity- Do not release into environment. May cause long term adverse effects.

Persistence and degradability- N/A Bioaccumulative potential- N/A

Mobility in Soil- N/A

### Component Ecotoxicity

Petroleum distillates, hydrotreated light

96 Hr LC50 Pimephales promelas: 45 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 2.2 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 2.4 mg/L

[static]

## Section 13 - Disposal Considerations

Dispose of in accordance with federal, state and local regulations. Controlled incineration is recommended for disposal of unused product. Prevent contamination of soil, drains and surface waters. Dispose of large containers to a licensed reconditioner. Dispose of small containers in compliance with local regulations.

Section 14 - Transport Information				
Agency	Proper Shipping Name	UN Number	Packing Group	<b>Hazard Class</b>
DOT	PRINTING INK	UN1210	II	3
DOT - LQ	PRINTING INK	UN1210	II	3
	LTD QTY			
IATA	PRINTING INK	UN1210	II	3
	Pkg Instr: Y341/353/364			
IMDG	PRINTING INK	UN1210	II	3
	EmS: F-E, S-D			
IMDG - LQ	PRINTING INK	UN1210	II	3
	LTD QTY			

## Section 15 - Regulatory Information

The following chemicals are listed in California Title 8 CCR Sections as Hazardous Substances

- None

The following chemicals are listed in California Title 8 CCR Sections 5200-5220 as Carcinogens .

- None

The following chemicals are listed in California Title 8 CCR Section 5203 as Carcinogens

- None

The following chemicals are listed in California Title 8 CCR Section 5209 as Carcinogens .

- None

The following chemicals are listed in the EU-Substances of Very High Concern (2008/67/ED) (SVHC):

- None

SDS for: D-1213 Page 6 of 8

The following chemicals are listed in the EU-Restriction of the use of certain Hazardous Substances (2011/65/EU) (RoHS):

- None

The following chemicals are included in the Global Automotive Declarable Substance List (GADSL)

- None

The following substances are required for notification by the Japanese Enforcement Order of the Industrial Safety and Health Law (ISHL):

13463-67-7 Titanium (IV) dioxide

64742-49-0 Naphtha, petroleum, hydrotreated light

64742-47-8 Petroleum distillates, hydrotreated light

The following chemicals are listed on the Massachusetts Right-to-Know Hazardous Substances List. 13463-67-7 Titanium (IV) dioxide

The following chemicals are listed on the New Jersey Right-to-Know Hazardous Substances List. 13463-67-7 Titanium (IV) dioxide

The following chemicals are listed on the Pennsylvania Right-to-Know Hazardous Substances List. 13463-67-7 Titanium (IV) dioxide

The following chemicals are listed by the State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

- None

Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 (EPCRA) requires certain facilities manufacturing, processing, or otherwise using listed toxic chemicals to report their environmental releases of such chemicals annually. The following chemicals are listed:

- None

The following chemicals are listed in EPCRA (SARA) Section 313: Persistent, Bioaccumulative, and Toxic Chemicals (PBT)

- None

The following chemicals are listed under EPCRA (SARA) Section 313: Toxic Release Inventory (TRI)

- None

Under Section 12(b) of the Toxic Substances Control Act (TSCA), exporters may need to notify the U.S. Environmental Protection Agency if they export or intend to export a product containing a chemical substance that is present on this list. The following substances are contained within this material:

- None

The following chemicals are listed as a Hazardous Air Pollutant under listed under the U.S. CAA (Clean Air Act)

- None

Country	<u>Regulation</u>	All Components Listed
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Canadian Domestic Substances List (DSL)	Yes
Canada	Canadian Non-Domestic Substances List (NSDL)	No
China	Inventory of Existing Chemical Substances Produced or Imported in China (IECSC	C) Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Europe	REACH Registered or Pre-Registered Substances and Intermediates	Yes
Japan	Japanese Inventory of Existing and New Chemical Substances (ENCS)	No
Japan	Japan Inventory of Industrial Safety and Health Law Substances (ISHL)	No
Korea	Korean Existing Chemical Inventory (KECI)	Yes

SDS for: D-1213 Page 7 of 8

New ZealandNew Zealand Inventory of Chemicals (NZIoC)YesPhilippinesPhilippines Inventory of Chemicals and Chemical Substances (PICCS)YesUSAToxic Substances and Control Act (TSCA)Yes

#### **EU Risk Phrases**

Not Available

#### **Safety Phrase**

Not Available

### Section 16 - Other Information

NFPA and HMIS use a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates extreme danger. Although similar, the two rating systems are intended for different purposes, and use different criteria. The NFPA system was developed to provide an on-the-spot alert to the hazards of a material, and their severity, to emergency responders. The HMIS system was designed to communicate workplace hazard information to employees who handle hazardous chemicals.


#### **Hazardous Material Information System (HMIS)**

## National Fire Protection Association (NFPA)



HMIS & NFPA Hazard Rating Legend \* = Chronic Health Hazard 0 = INSIGNIFICANT 1 = SLIGHT 2 = MODERATE

3 = HIGH



The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

Date revised: 2021-09-13 Revision No:
Date Prepared: 9/13/2021 Reviewer ID: apalmer

SDS for: D-1213 Page 8 of 8