



Safety Data Sheet

Issue Date: 10-Feb-2009

Revision Date: 23-Feb-2021

Version 1

1. IDENTIFICATION

Product identifier

Product Name Type M Blue

Other means of identification

SDS # USM-007

Product Code IU-M44, IU-M4QT, IU-M4QTH, IU-M4GL
UN/ID No UN1210

Recommended use of the chemical and restrictions on use

Recommended Use Printing ink.

Details of the supplier of the safety data sheet

Manufacturer Address
PANNIER CORPORATION
207 Sandusky Street
Pittsburgh, PA 15212-5823
PH: 412-323-4900
Email: sales@pannier.com

Emergency telephone number

Emergency Telephone INFOTRAC: 1-800-535-5053

2. HAZARDS IDENTIFICATION

Appearance Blue liquid

Physical state Liquid

Odor Alcohol

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 1A
Flammable liquids	Category 2

Signal Word

Danger

Hazard statements

Causes skin irritation
Causes serious eye damage
May cause cancer
Highly flammable liquid and vapor



Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Use explosion-proof equipment

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Immediately call a poison center or doctor/physician
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 If skin irritation occurs: Get medical advice/attention
 Wash contaminated clothing before reuse
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Harmful to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
Ethanol	64-17-5	27-32
Titanium dioxide	13463-67-7	25-28
Glycol Ether EB	111-76-2	23-26
n-Propyl Alcohol	71-23-8	9-11
Methylisobutyl ketone	108-10-1	1-2
Cellulose nitrate	9004-70-0	0.3-2
Solvent naphtha (petroleum), light aliphatic	64742-89-8	<1
N-Heptane	142-82-5	<1
n-Butyl acetate	123-86-4	<1
Toluene	108-88-3	Trace
Acetaldehyde	75-07-0	Trace

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**Description of first aid measures****Eye Contact**

Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.
 Get immediate medical advice/attention.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If irritation persists or feeling unwell, obtain medical advice.

Inhalation	Remove exposed individual(s) to fresh air for 20 minutes. Consult a physician/poison center if individual's condition declines or if symptoms persist.
Ingestion	Do not induce vomiting without medical advice. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Seek medical attention immediately.

Most important symptoms and effects, both acute and delayed

Symptoms	Causes skin irritation and serious eye damage. May be harmful if swallowed. May be harmful in contact with skin. May cause irritation to the mucous membranes and upper respiratory tract.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Water fog or fine spray, carbon dioxide, dry chemical or foam.

Unsuitable Extinguishing Media Direct water stream may spread fire.

Specific Hazards Arising from the Chemical

Highly flammable liquid and vapor. Vapors may travel to source of ignition and flash back.

Hazardous combustion products Carbon oxides.

Explosion Data

Sensitivity to Static Discharge May be ignited by heat, sparks or flames. Take precautionary measures against static discharge.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Personal Precautions Wear protective clothing as described in Section 8 of this safety data sheet. Remove all sources of ignition & ventilate area. Evacuate unnecessary personnel.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Soak up and contain spill with an inert (i.e. vermiculite, dry sand or earth) absorbent material.

Methods for Clean-Up Use clean non-sparking tools to collect absorbed material. Sweep up absorbed material and shovel into suitable containers for disposal. Discard any product, residue, disposable container or liner in full compliance with federal, state, and local regulations. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling

Handle in accordance with good industrial hygiene and safety practice. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when handling this product. Use personal protection recommended in Section 8. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only with adequate ventilation. Ground/bond container and receiving equipment. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Use spark-proof tools and explosion-proof equipment. Keep container tightly closed. Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible Materials

Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethanol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m ³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m ³
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³ TWA: 2.4 mg/m ³ CIB 63 fine TWA: 0.3 mg/m ³ CIB 63 ultrafine, including engineered nanoscale
Glycol Ether EB 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
n-Propyl Alcohol 71-23-8	TWA: 100 ppm	TWA: 200 ppm TWA: 500 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 500 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 625 mg/m ³	IDLH: 800 ppm TWA: 200 ppm TWA: 500 mg/m ³ STEL: 250 ppm STEL: 625 mg/m ³
Methylisobutyl ketone 108-10-1	STEL: 75 ppm TWA: 20 ppm	TWA: 100 ppm TWA: 410 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 205 mg/m ³ (vacated) STEL: 75 ppm (vacated) STEL: 300 mg/m ³	IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m ³ STEL: 75 ppm STEL: 300 mg/m ³
n-Butyl acetate 123-86-4	STEL: 150 ppm TWA: 50 ppm	TWA: 150 ppm TWA: 710 mg/m ³ (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m ³ (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m ³	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³
N-Heptane 142-82-5	STEL: 500 ppm TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 2000 mg/m ³	IDLH: 750 ppm Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m ³ 15 min TWA: 85 ppm TWA: 350 mg/m ³
n-Propyl acetate	STEL: 150 ppm	TWA: 200 ppm	IDLH: 1700 ppm

109-60-4	TWA: 100 ppm	TWA: 840 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 840 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 1050 mg/m ³	TWA: 200 ppm TWA: 840 mg/m ³ STEL: 250 ppm STEL: 1050 mg/m ³
Acetaldehyde 75-07-0	Ceiling: 25 ppm	TWA: 200 ppm TWA: 360 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 180 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 270 mg/m ³	IDLH: 2000 ppm
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³

Appropriate engineering controls**Engineering Controls**

Apply technical measures to comply with the occupational exposure limits. Maintain eye wash fountain and quick-drench facilities in work area. Local exhaust ventilation recommended.

Individual protection measures, such as personal protective equipment**Eye/Face Protection**

Use safety glasses or chemical splash goggles. Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin and Body Protection

Gloves are recommended. Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection

MSHA/ NIOSH-approved vapor respirator is recommended with handling in areas where adequate ventilation is not available. Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations

Avoid contact with skin, eyes and clothing. After handling this product, wash hands before eating, drinking, or smoking. If contact occurs, remove contaminated clothing. If needed, take first aid action shown on section 4 of this SDS. Launder contaminated clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid	Odor	Alcohol
Appearance	Blue liquid	Odor Threshold	Not determined
Color	Blue		
<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>	
pH	Not determined		
Melting point / freezing point	Not determined		
Boiling point / boiling range	Not determined		
Flash point	15.72 °C / 70 °F		
Evaporation Rate	Not determined		
Flammability (Solid, Gas)	Not determined		
Flammability Limit in Air			
Upper flammability or explosive limits	Not determined		
Lower flammability or explosive limits	Not determined		
Vapor Pressure	Not determined		
Vapor Density	Heavier than air	.? (air = 1)	

Relative Density	Not determined
Water Solubility	Not determined
Solubility in other solvents	Not determined
Partition Coefficient	Not determined
Autoignition temperature	Not determined
Decomposition temperature	Not determined
Kinematic viscosity	Not determined
Dynamic Viscosity	Not determined
Explosive Properties	Not determined
Oxidizing Properties	Not determined

Other information

VOC Content (%)	58.64
Liquid Density	8.75 lbs./gal

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Heat, sparks and open flames.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

Eye Contact	Avoid contact with eyes.
Skin Contact	May be harmful in contact with skin.
Inhalation	Avoid inhalation.
Ingestion	May be harmful if swallowed.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Ethanol 64-17-5	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat) 4 h
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Glycol Ether EB 111-76-2	= 470 mg/kg (Rat)	= 435 mg/kg (Rabbit)	= 486 ppm (Rat) 4 h = 450 ppm (Rat) 4 h
n-Propyl Alcohol	= 1870 mg/kg (Rat)	= 4049 mg/kg (Rabbit)	> 13548 ppm (Rat) 4 h

71-23-8			
Cellulose nitrate 9004-70-0	> 5 g/kg (Rat)	-	-
Methylisobutyl ketone 108-10-1	= 2080 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	2000 - 4000 ppm (Rat) 4 h
n-Butyl acetate 123-86-4	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat) 4 h
N-Heptane 142-82-5	-	= 3000 mg/kg (Rabbit)	= 103 g/m ³ (Rat) 4 h
Solvent naphtha (petroleum), light aliphatic 64742-89-8	-	= 3000 mg/kg (Rabbit)	-
n-Propyl acetate 109-60-4	= 8700 mg/kg (Rat)	> 17756 mg/kg (Rabbit)	-
Acetaldehyde 75-07-0	= 660 mg/kg (Rat)	= 3540 mg/kg (Rabbit)	= 13000 ppm (Rat) 4 h
Toluene 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye damage.

Carcinogenicity May cause cancer. Ethanol has been shown to be carcinogenic in long-term studies only when consumed as an alcoholic beverage. Titanium dioxide is a possible carcinogen when it appears as a respirable dust.

Chemical name	ACGIH	IARC	NTP	OSHA
Ethanol 64-17-5	A3	Group 1	Known	X
Titanium dioxide 13463-67-7		Group 2B		X
Glycol Ether EB 111-76-2	A3	Group 3		
Cellulose nitrate 9004-70-0		Group 2A		X
Methylisobutyl ketone 108-10-1	A3	Group 2B		X
Acetaldehyde 75-07-0	A2	Group 1 Group 2B	Reasonably Anticipated	X
Toluene 108-88-3		Group 3		

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

NTP (National Toxicology Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document.

Oral LD50 3,033.90 mg/kg
 Dermal LD50 3,701.00 mg/kg
 ATEmix (inhalation-dust/mist) 5.28 mg/L

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Component Information

Chemical name	Algae/aquatic plants	Fish	Crustacea
Ethanol 64-17-5		13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through 12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static 100: 96 h Pimephales promelas mg/L LC50 static	10800: 24 h Daphnia magna mg/L EC50 2: 48 h Daphnia magna mg/L EC50 Static 9268 - 14221: 48 h Daphnia magna mg/L LC50
Glycol Ether EB 111-76-2		2950: 96 h Lepomis macrochirus mg/L LC50 1490: 96 h Lepomis macrochirus mg/L LC50 static	1000: 48 h Daphnia magna mg/L EC50 1698 - 1940: 24 h Daphnia magna mg/L EC50
n-Propyl Alcohol 71-23-8		4480: 96 h Pimephales promelas mg/L LC50 flow-through	3642: 48 h Daphnia magna mg/L EC50 3339 - 3977: 48 h Daphnia magna mg/L EC50 Static
Methylisobutyl ketone 108-10-1	400: 96 h Pseudokirchneriella subcapitata mg/L EC50	496 - 514: 96 h Pimephales promelas mg/L LC50 flow-through	170: 48 h Daphnia magna mg/L EC50
n-Butyl acetate 123-86-4	674.7: 72 h Desmodesmus subspicatus mg/L EC50	100: 96 h Lepomis macrochirus mg/L LC50 static 17 - 19: 96 h Pimephales promelas mg/L LC50 flow-through 62: 96 h Leuciscus idus mg/L LC50 static	72.8: 24 h Daphnia magna mg/L EC50
N-Heptane 142-82-5		375.0: 96 h Cichlid fish mg/L LC50	10: 24 h Daphnia magna mg/L EC50
Solvent naphtha (petroleum), light aliphatic 64742-89-8	4700: 72 h Pseudokirchneriella subcapitata mg/L EC50		
n-Propyl acetate 109-60-4		56 - 64: 96 h Pimephales promelas mg/L LC50 static 56 - 64: 96 h Pimephales promelas mg/L LC50 flow-through	318: 24 h Daphnia magna mg/L EC50
Acetaldehyde 75-07-0	237 - 249: 120 h Nitzschia linearis mg/L EC50	28.0 - 34.0: 96 h Pimephales promelas mg/L LC50 flow-through 39.8 - 46.8: 96 h Pimephales promelas mg/L LC50 static 53: 96 h Lepomis macrochirus mg/L LC50 static 1.8 - 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static	3.64 - 6.15: 48 h Daphnia magna mg/L EC50 Static 48.3: 48 h Daphnia magna mg/L EC50
Toluene 108-88-3	12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 433: 96 h Pseudokirchneriella subcapitata mg/L EC50	12.6: 96 h Pimephales promelas mg/L LC50 static 15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static 54: 96 h Oryzias latipes mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static	11.5: 48 h Daphnia magna mg/L EC50 5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static

Persistence/Degradability

Not determined.

Bioaccumulation

There is no data for this product.

Mobility

Chemical name	Partition coefficient
Ethanol 64-17-5	-0.32
Glycol Ether EB 111-76-2	0.81
n-Propyl Alcohol 71-23-8	0.34
Methylisobutyl ketone 108-10-1	1.19
N-Heptane 142-82-5	4.66
n-Butyl acetate 123-86-4	1.81
Toluene 108-88-3	2.7
Acetaldehyde 75-07-0	0.5

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS**Waste Treatment Methods****Disposal of Wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

D001

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methylisobutyl ketone 108-10-1		Included in waste stream: F039		U161
Acetaldehyde 75-07-0				U001
Toluene 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151		U220

Chemical name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene 108-88-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These	

			chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	
--	--	--	---	--

California Hazardous Waste Status

Chemical name	California Hazardous Waste Status
Ethanol 64-17-5	Toxic Ignitable
n-Propyl Alcohol 71-23-8	Toxic Ignitable
Cellulose nitrate 9004-70-0	Ignitable in ether and alcohol Reactive in ether and alcohol
N-Heptane 142-82-5	Toxic Ignitable
n-Butyl acetate 123-86-4	Toxic
Toluene 108-88-3	Toxic Ignitable
Acetaldehyde 75-07-0	Toxic Ignitable

14. TRANSPORT INFORMATION**Note**

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No UN1210
 Proper Shipping Name Printing ink
 Hazard class 3
 Packing Group II

IATA

UN number UN1210
 Proper Shipping Name Printing ink
 Transport hazard class(es) 3
 Packing Group II

IMDG

UN number UN1210
 Proper Shipping Name Printing ink
 Transport hazard class(es) 3
 Packing Group II

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	TSCA Inventory Status	DSL/NDSL	EINECS/ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Ethanol	X	ACTIVE	X	X	X	X	X	X	X
Titanium dioxide	X	ACTIVE	X	X	X	X	X	X	X
Glycol Ether EB	X	ACTIVE	X	X	X	X	X	X	X
n-Propyl Alcohol	X	ACTIVE	X	X	X	X	X	X	X
Cellulose nitrate	X	ACTIVE	X		X	X	X	X	X
Methylisobutyl ketone	X	ACTIVE	X	X	X	X	X	X	X
n-Butyl acetate	X	ACTIVE	X	X	X	X	X	X	X
N-Heptane	X	ACTIVE	X	X	X	X	X	X	X
Solvent naphtha (petroleum), light aliphatic	X	ACTIVE	X	X		X	X	X	X
n-Propyl acetate	X	ACTIVE	X	X	X	X	X	X	X
Acetaldehyde	X	ACTIVE	X	X	X	X	X	X	X
Toluene	X	ACTIVE	X	X	X	X	X	X	X

Legend:*TSCA - United States Toxic Substances Control Act Section 8(b) Inventory**DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List**EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances**ENCS - Japan Existing and New Chemical Substances**IECSC - China Inventory of Existing Chemical Substances**KECL - Korean Existing and Evaluated Chemical Substances**PICCS - Philippines Inventory of Chemicals and Chemical Substances**AICS - Australian Inventory of Chemical Substances***US Federal Regulations****CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Methylisobutyl ketone 108-10-1	5000 lb.		RQ 5000 lb. final RQ RQ 2270 kg final RQ
n-Butyl acetate 123-86-4	5000 lb.		RQ 5000 lb. final RQ RQ 2270 kg final RQ
Acetaldehyde 75-07-0	1000 lb.		RQ 1000 lb. final RQ RQ 454 kg final RQ
Toluene 108-88-3	1000 lb. 1 lb.		RQ 1000 lb. final RQ RQ 454 kg final RQ RQ 1 lb. final RQ RQ 0.454 kg final RQ

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Glycol Ether EB - 111-76-2	111-76-2	23-26	1.0
Methylisobutyl ketone - 108-10-1	108-10-1	1-2	1.0
Acetaldehyde - 75-07-0	75-07-0	Trace	0.1
Toluene - 108-88-3	108-88-3	Trace	1.0

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
n-Butyl acetate	5000 lb.			X
Toluene	1000 lb.	X	X	X
Acetaldehyde	1000 lb.			X

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Ethanol - 64-17-5	Carcinogen Developmental
Titanium dioxide - 13463-67-7	Carcinogen
Methylisobutyl ketone - 108-10-1	Carcinogen Developmental
Toluene - 108-88-3	Developmental
Acetaldehyde - 75-07-0	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Ethanol 64-17-5	X	X	X
Titanium dioxide 13463-67-7	X	X	X
Glycol Ether EB 111-76-2	X	X	X
n-Propyl Alcohol 71-23-8	X	X	X
Methylisobutyl ketone 108-10-1	X	X	X
Cellulose nitrate 9004-70-0	X	X	X
n-Propyl acetate 109-60-4	X	X	X
n-Butyl acetate 123-86-4	X	X	X
N-Heptane 142-82-5	X	X	X
Acetaldehyde 75-07-0	X	X	X
Toluene 108-88-3	X	X	X

16. OTHER INFORMATION**NFPA****Health Hazards****Flammability****Instability****Special Hazards****HMIS****Health Hazards****Flammability****Physical hazards****Personal Protection**Not determined
2Not determined
3Not determined
0Not determined
Not determined**Issue Date:** 10-Feb-2009**Revision Date:** 23-Feb-2021**Revision Note:** New format**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet